

## P-W & SHW SERIES



**COXREELS** P-W and SHW Series spring driven "Welding" hose reels are the ideal solution for managing bulky twin line welding hose. The P-W Series, like the P Series, is more compact in size and shares the reputation for long lasting performance. The SHW Series has a larger chassis and frame to accommodate longer lengths of welding hose and Coxreels' original Super Hub dual axle support system for increased stability during operation, less vibration and greater structural integrity.

### SWIVEL

- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel
- Swivel lock bracket ensures maximum safety
- Swivel Seals: VITON®

### DESIGN & STRUCTURE

- Designed for Oxy-Acetylene or "T" grade welding hose
- Single pedestal reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Coxreels' exclusive Super Hub™ dual axle support system on models with size index #2 & #3

### RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position non-sparking lock ratchet mechanism secures hose at desired length

### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat finish
- CNC robotically spun and ribbed discs with rolled edges provide strength, safety, and durability
- Industry leading 2 year manufacturer's limited warranty
- Made in the U.S.A. – Sold & Supported Worldwide

### POSSIBLE FIELDS OF APPLICATION

- Manufacturing Plant
- Maintenance, Repair & Operations
- Welding/Service Trucks
- Welding Shops
- Garage Settings
- Automotive & Fleet Maintenance
- Pipelines
- Mining, Construction & Railroad Operations

MODELS

ACCESSORIES

VIDEOS

## TECHNICAL DOCUMENTS

- Product manual - [DOWNLOAD](#)
- Exploded drawings - [DOWNLOAD](#)



Click "Add to Quote" to view compatible accessories

## HOSE FILTER

Show results with or without Hose

Y  N [RESET SELECTION](#)

## OXYGEN-ACETYLENE WELDING HOSE REELS

Reels Hose supplied on reel is twin-siamese type meeting R.M.A. and C.G.A. type V.D. grade R specifications. Use of other types of hose is not recommended. **Note: Do Not Exceed Listed Hose O.D. To Obtain Max. Length.**

REEL			SPECS				SIZE INDEX						
MODEL	LBS	HOSE	I.D.	O.D.	FT.	PSI	W	H	L	X	Y	M	N
						Overall Dimensions			Base		Mounting Pattern		
P-W-125	46	Y	1/4"	"	25	200	8-1/2"	18-5/8"	17"	6"	6"	4"	6"

Add to Quote

P-WL-125	39	N	1/4"	"	25	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
P-W-135	48	Y	1/4"	"	35	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
P-WL-135	40	N	1/4"	"	35	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
P-W-140	51	Y	1/4"	"	40	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
P-WL-140	42	N	1/4"	"	40	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
SHW-N-150	64	Y	1/4"	"	50	200	10-1/4"	21-1/4"	19-1/2"	6"	6"	4"	5"	Add to Quote
SHWL-N-150	52	N	1/4"	"	50	200	10-1/4"	21-1/4"	19-1/2"	6"	6"	4"	5"	Add to Quote
SHW-N-160	76	Y	1/4"	"	50	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWL-N-160	61	N	1/4"	"	60	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHW-N-175	80	Y	1/4"	"	75	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWL-N-175	63	N	1/4"	"	75	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHW-N-1100	84	Y	1/4"	"	100	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWL-N-1100	62	N	1/4"	"	100	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote

▶ See **EZ-COIL** offering

## DUAL FUEL GAS HOSE REELS

Hose supplied on reel is twin-siamese type grade "T." Grade "T" reels and hoses are used for a wide variety of gases, such as MAPP, propane, natural and fuel. **Note: Do Not Exceed Listed Hose O.D. To Obtain Max. Length.**

REEL			SPECS				SIZE INDEX							
MODEL	LBS	HOSE	I.D.	O.D.	FT.	PSI	W	H	L	X	Y	M	N	Add to Quote
							Overall Dimensions			Base		Mounting Pattern		
P-WT-125	46	Y	1/4"	"	25	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
P-WTL-125	39	N	1/4"	"	25	200	8-1/2"	18-5/8"	17"	6"	6"	4"	5"	Add to Quote
SHWT-N-150	64	Y	1/4"	"	50	200	10-1/4"	21-1/4"	19-1/2"	6"	6"	4"	5"	Add to Quote
SHWTL-N-150	52	N	1/4"	"	50	200	10-1/4"	21-1/4"	19-1/2"	6"	6"	4"	5"	Add to Quote
SHWT-N-175	80	Y	1/4"	"	75	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWTL-N-175	63	N	1/4"	"	75	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWT-N-1100	84	Y	1/4"	"	100	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote
SHWTL-N-1100	62	N	1/4"	"	100	200	10-1/4"	25-1/2"	24"	6"	6"	4"	5"	Add to Quote

▶ See **EZ-COIL** offering



### USA Made, Quality & Support

We take great pride in designing, building and supplying the world's finest reels made right here in the U.S.A.



### 2 Year Warranty

Coxreels proudly stands behind our reels as they are built to last!

#### PRODUCTS

Spring Driven

EZ-Coil®

Hand Crank

Motor Driven

Spring Driven & EZ-Coil® Accessories

Hand Crank & Motor Driven Accessories

#### INDUSTRIES

NEW RELEASES

LITERATURE

KNOWLEDGE CENTER

ABOUT COXREELS

#### REQUEST A QUOTE

FIND A DISTRIBUTOR

CONTACT US

Toll Free **800-269-7335**

Fax **800-229-7335**

Email [info@coxreels.com](mailto:info@coxreels.com)

5865 S. Ash Ave.  
Tempe, AZ 85283

Copyright © 2015 Coxreels  
Privacy Policy | Terms & Conditions

